












Product comparison tables










Network video

Axis fixed network cameras

	AXIS M10 Series				AXIS M11 Series				
	AXIS M1011	AXIS M1011-W	AXIS M1031-W	AXIS M1054	AXIS M1103	AXIS M1104	AXIS M1113 ^(a) AXIS M1113-E ^(b)	AXIS M1114 ^(a) AXIS M1114-E ^(b)	AXIS 221
									
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CCD
Lens	4.4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	2.9 mm/F2.0 fixed iris	Fixed iris, CS mount 2.8 mm/F2.0 6 mm/F1.8	Fixed iris, CS mount 2.8 mm/F2.0 6 mm/F1.8	Varifocal 2.9 - 8.2 mm/F1.4 DC-iris, CS mount	Varifocal 2.8 - 8 mm/F1.2 DC-iris, CS mount	Varifocal 3 - 8 mm/F1.0 DC-iris, CS mount
Horizontal angle of view	47°	47°	47°	80°	2.8 mm: 66° 6 mm: 31°	2.8 mm: 80° 6 mm: 37°	65° - 25°	77° - 29°	93° - 35°
Day and night									Automatic
Min illumination/light sensitivity (lux)	1 - 10,000	1 - 10,000	1 - 10,000 0 with LED on	1.2 - 100,000 0 with LED on	2.8 mm: 1.0 - 100,000 6 mm: 0.9 - 100,000	2.8 mm: 1.0 - 100,000 6 mm: 0.9 - 100,000	0.6	0.6	0.65 (color) 0.08 (B/W)
Video compression	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	MPEG-4 Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	640 x 480	1280 x 800 (1 MP)	800 x 600	1280 x 800 (1 MP) ⁽²⁾	800 x 600	1280 x 800 (1 MP) ⁽²⁾	640 x 480
Frames per second	30 (640x480)	30 (640x480)	30 (640x480)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	45 (640x480) 60 (480x360)
Audio support			Two-way Built-in mic and speaker	Two-way Built-in mic and speaker					
Alarm in-/outputs				1/1					2/1
Intelligent video	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm
Security	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC PoE splitter available	DC PoE splitter available	DC PoE splitter available	DC PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	AC/DC PoE IEEE 802.3af Class 2
Serial connectors									RS-232, RS-485
Outdoor use					Requires housing	Requires housing	Outdoor ready ^(b)	Outdoor ready ^(b)	Requires housing
Other	AVHS ⁽¹⁾ , ONVIF	Wireless, AVHS ⁽¹⁾ , ONVIF	Built-in PIR sensor, illumination LED, wireless, AVHS ⁽¹⁾ , ONVIF	Built-in PIR sensor, illumination LED, digital PTZ, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™ ^(a)	Digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™ ^(a)	Corridor Format™ (3:4 only) AVHS ⁽³⁾
Axis Part #	0302-004	0301-004	0300-004	0338-004	2.8mm: 0329-001 6mm: 0366-001	2.8mm: 0339-001 6mm: 0367-001	0340-001 ^(a) 0431-001 ^(b)	0341-001 ^(a) 0432-001 ^(b)	0221-004
MSRP	\$179	\$199	\$279	\$399	2.8mm: \$349 6mm: \$349	2.8mm: \$449 6mm: \$449	\$449 ^(a) \$549 ^(b)	\$549 ^(a) \$649 ^(b)	\$999









Axis fixed network cameras

Axis covert cameras

	AXIS P13 Series				AXIS Q16 Series		AXIS Q17 Series	AXIS P85 Series	
	AXIS P1343^(a) AXIS P1343-E^(b)	AXIS P1344^(a) AXIS P1344-E^(b)	AXIS P1346^(a) AXIS P1346-E^(b)	AXIS P1347^(a) AXIS P1347-E^(b)	AXIS Q1602^(a) AXIS Q1602-E^(b)	AXIS Q1604^(a) AXIS Q1604-E^(b)	AXIS Q1755^(a) AXIS Q1755-E^(b)	AXIS P8513	AXIS P8514
									
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" (effective) progressive scan CMOS	1/2.5" progressive scan CMOS	1/3" progressive scan CMOS	1/3" progressive scan CMOS	1/3" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS
Lens	Varifocal 3 - 8 mm/F1.0 DC-iris, CS mount Remote back focus	Varifocal 3 - 8 mm/F1.2 DC-iris, CS mount Remote back focus	Varifocal 3.5 - 10 mm/F1.6 P-Iris ⁽¹⁾ , CS mount Remote back focus	Varifocal 3.5 - 10 mm/F1.6 P-Iris ⁽¹⁾ , CS mount Remote back focus	Varifocal 2.8 - 8 mm/F1.2 DC-iris, CS mount Remote back focus	Varifocal 2.8 - 8 mm/F1.2 DC-iris, CS mount Remote back focus	5.1 - 51 mm/F1.8 auto iris and autofocus 10x optical zoom 12x digital zoom	3.7 mm/F1.8 fixed iris	3.7 mm/F1.8 fixed iris
Horizontal angle of view	61° - 21°	66° - 27°	72° - 27°	89° - 33°	100° - 34° ^(a) 80° - 34° ^(b)	100° - 34° ^(a) 80° - 34° ^(b)	50° - 5.4°	48°	57°
Day and night	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic		
Min illumination/light sensitivity (lux)	0.2 (color) 0.05 (B/W)	0.3 (color) 0.05 (B/W)	0.5 (color) 0.08 (B/W)	0.5 (color) 0.08 (B/W)	0.05 (color) 0.008 (B/W)	0.1 (color) 0.02 (B/W)	2 (color) 0.2 (B/W)	1 - 100,000	1 - 100,000
Video compression	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	800 x 600	1280 x 800 (1 MP) ⁽³⁾	2048 x 1536 (3 MP)	2560 x 1920 (5 MP)	768 x 576	1280 x 960 (1 MP) ⁽⁴⁾	HDTV 1080i (2 MP)	800 x 600	1280 x 800 (1 MP) ⁽³⁾
Frames per second	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	20 (2048x1536) 30 (HDTV 1080p) 30 (1600x1200)	12 (2560x1920) 20 (2048x1536) 30 (HDTV 1080p)	30 (768x576)	30 (1280x960) 30 (HDTV 720p)	30/25 (HDTV 1080i) 30/25 (HDTV 720p)	30 (800x600) 30 (HDTV 720p)	30 (1280x800) 30 (HDTV 720p)
Audio support	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)	Two-way, Built-in mic ^(a)
Alarm in-/outputs	1/1	1/1	1/1	1/1	1/1	1/1	2 configurable inputs/outputs		
Intelligent video	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm Gatekeeper	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC ^(a) PoE IEEE 802.3af Class 2 ^(a) PoE Class 3/High PoE ^(b)	DC ^(a) PoE IEEE 802.3af Class 2 ^(a) PoE Class 3/High PoE ^(b)	DC ^(a) PoE IEEE 802.3af Class 3 ^(a,b) High PoE ^(b)	DC ^(a) PoE IEEE 802.3af Class 3 ^(a,b) High PoE ^(b)	PoE IEEE 802.3af Class 3 ^(a,b) High PoE ^(b)	PoE IEEE 802.3af Class 3 ^(a,b) High PoE ^(b)	AC/DC ^(a) PoE IEEE 802.3af Class 3 ^(a,b) High PoE ^(b)	PoE IEEE 802.3af Class 3 High PoE	PoE IEEE 802.3af Class 3 High PoE
Serial connectors							RS-422/RS-485		
Outdoor use	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)		
Other	WDR, digital PTZ, pixel counter, SD/SDHC card slot IP66 and NEMA 4X ratings ^(b) , AVHS ⁽²⁾ , ONVIF, Corridor Format ^{TM(a)}	WDR, digital PTZ, pixel counter, SD/SDHC card slot IP66 and NEMA 4X ratings ^(b) , AVHS ⁽²⁾ , ONVIF, Corridor Format ^{TM(a)}	WDR, digital PTZ, pixel counter, multi-view streaming, SD/SDHC card slot, IP66 and NEMA 4X ratings ^(b) , AVHS ⁽²⁾ , ONVIF, Corridor Format ^{TM(a)}	WDR, digital PTZ, pixel counter, multi-view streaming, SD/SDHC card slot, IP66 and NEMA 4X ratings ^(b) , AVHS ⁽²⁾ , ONVIF, Corridor Format ^{TM(a)}	WDR, pixel counter, SD/SDHC card slot, Lightfinder technology, AVHS ⁽²⁾ , ONVIF, Corridor Format TM	WDR-Dynamic capture, pixel counter, SD/SDHC card slot, AVHS ⁽²⁾ , ONVIF, Corridor Format TM	SD/SDHC card slot, analog video out, pan/tilt head support IP66 and NEMA 4X ratings ^(b) , ONVIF, Corridor Format ^{TM(a)}	Eye-level covert camera, digital PTZ, pixel counter, AVHS ⁽²⁾ , ONVIF, Available in white ^(a) , black ^(b) , and chrome ^(c)	Eye-level covert camera, digital PTZ, pixel counter, AVHS ⁽²⁾ , ONVIF, Available in white ^(a) , black ^(b) , and chrome ^(c)
Axis Part #	0320-001 ^(a) 0349-001 ^(b)	0324-001 ^(a) 0350-001 ^(b)	0328-001 ^(a) 0351-001 ^(b)	0343-001 ^(a) 0368-001 ^(b)	0437-001 ^(a) 0438-001 ^(b)	0439-001 ^(a) 0463-001 ^(b)	0304-001 ^(a) 0348-001 ^(b)	0451-004 ^(a) 0452-004 ^(b) 0453-004 ^(c)	0454-004 ^(a) 0455-004 ^(b) 0456-004 ^(c)
MSRP	\$749 ^(a) \$999 ^(b)	\$849 ^(a) \$1099 ^(b)	\$1099 ^(a) \$1399 ^(b)	\$1269 ^(a) \$1569 ^(b)	\$999 ^(a) \$1299 ^(b)	\$999 ^(a) \$1299 ^(b)	\$1499 ^(a) \$1799 ^(b)	\$999 ^(a) , \$999 ^(b) , \$999 ^(c)	\$1099 ^(a) , \$1099 ^(b) , \$1099 ^(c)










Notations (a) and (b) refer to the corresponding product models for the column; (1) AXIS P1346-E and AXIS 1347-E also support DC-iris lens; (2) AVHS - AXIS Video Hosting System with One-Click Camera Connection; (3) 1440 x 900 (1.3 MP) scaled resolution available via VAPIX[®]; (4) 1440x900 (1.4 MP) scaled resolution available in VAPIX(R)

Axis fixed dome network cameras

	AXIS M30 Series		AXIS M31-R Series		AXIS M31-VE Series		AXIS M32 Series	
	AXIS M3011	AXIS M3014	AXIS M3113-R	AXIS M3114-R	AXIS M3113-VE ^(a) AXIS M3113-VE Nocap ^(b)	AXIS M3114-VE ^(a) AXIS M3114-VE Nocap ^(b)	AXIS M3203 ^(a) AXIS M3203-V ^(b)	AXIS M3204 ^(a) AXIS M3204-V ^(b)
								
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS
Lens	3.0 mm/F2.0 fixed iris	2.8 mm/F2.0 fixed iris	2.9 mm/F2.0 fixed iris	Fixed iris Standard: 2.9 mm/F2.0 2 mm:1.97 mm/F3.0	2.9 mm/F2.0 fixed iris	Fixed iris Standard: 2.9 mm/F2.0 2 mm:1.97 mm/F3.0	Varifocal 2.8 - 10 mm/F1.7 fixed iris	Varifocal 2.8 - 10 mm/F1.7 fixed iris
Horizontal angle of view	66°	80°	66°	Standard: 80° 2 mm: 105°	66°	Standard: 80° 2 mm: 105°	66° - 18°	80° - 22°
Day and night								
Min illumination/light sensitivity (lux)	1 - 10,000	1 - 100,000	1 - 100,000	1 - 100,000	1 - 100,000	1 - 100,000	0.9 - 100,000	0.9 - 100,000
Video compression	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	640 x 480	1280 x 800 (1 MP)	800x600	1280x800 (1 MP) ⁽²⁾	800x600	1280x800 (1 MP) ⁽²⁾	800 x 600	1280 x 800 (1 MP) ⁽²⁾
Frames per second	30 (640x480)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)
Audio support								
Alarm in-/outputs								
Intelligent video	Motion detection Tampering alarm	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2
Serial connectors								
Outdoor use					Outdoor ready	Outdoor ready		
Other	Recessed mounting, pixel counter, AVHS ⁽¹⁾ , ONVIF	Recessed mounting, digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF	Rugged connectors for mobile surveillance, IP66, IP67 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Rugged connectors for mobile surveillance, IP66, IP67 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66, IP67 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66, IP67 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Tamper resistant ^(a) Vandal resistant ^(b) digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Tamper resistant ^(a) Vandal resistant ^(b) digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™
Axis Part #	0284-001	0285-001	0330-001	0342-001	0412-001 ^(a) , 0441-001 ^(b)	0413-001 ^(a) , 0442-001 ^(b)	0336-001 ^(a) , 0345-001 ^(b)	0337-001 ^(a) , 0346-001 ^(b)
MSRP	\$399	\$499	\$449	\$549	\$449 ^(a+b)	\$549 ^(a+b)	\$399 ^(a) , \$439 ^(b)	\$499 ^(a) , \$539 ^(b)

Notations (a) and (b) refer to the corresponding product models for the column; (1) AVHS - AXIS Video Hosting System with One-Click Camera Connection; (2) 1440 x 900 (1.3 MP) scaled resolution available via VAPIX®; (3) Special firmware needed. Available for partners on Partner Pages.









Axis fixed dome network cameras

	AXIS P33 Series								
	AXIS P3301 ^(a) AXIS P3301-V ^(b)	AXIS P3304 ^(a) AXIS P3304-V ^(b)	AXIS P3343 ^(a) AXIS P3343-V ^(b)	AXIS P3343-VE	AXIS P3344 ^(a) AXIS P3344-V ^(b)	AXIS P3344-VE	AXIS P3346 ^(a) AXIS P3346-V ^(b)	AXIS P3346-VE	AXIS P3353
									
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" (effective) progressive scan CMOS	1/3" (effective) progressive scan CMOS	Progressive scan RGB CMOS 1/3"
Lens	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.7 DC-iris	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.4 12 mm: 3.3-12 mm/F1.6	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.4 12 mm: 3.3-12 mm/F1.6	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.4 12 mm: 3.3-12 mm/F1.6	Varifocal, P-iris, remote focus and zoom 3-9 mm/F1.2	Varifocal, P-iris, remote focus and zoom 3-9 mm/F1.2	Varifocal, remote focus and zoom, IR correct, P-iris 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4
Horizontal angle of view	72° - 23°	80° - 22°	6 mm: 72° - 34° 12 mm: 54° - 17°	6 mm: 72° - 34° 12 mm: 54° - 17°	6 mm: 87° - 40° 12 mm: 70° - 20°	6 mm: 87° - 40° 12 mm: 70° - 20°	84° - 30°	84° - 30°	6 mm: 105° - 49° 12 mm: 82° - 24°
Day and night			Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	1	0.9	6 mm: 0.2 (color), 0.04 (B/W) 12 mm: 0.3 (color), 0.05 (B/W)	6mm: 0.1 (color), 0.02 (B/W) 12mm: 0.15 (color), 0.03 (B/W)	6 mm: 0.3 (color), 0.05 (B/W) 12 mm: 0.4 (color), 0.06 (B/W)	6 mm: 0.3 (color), 0.05 (B/W) 12 mm: 0.4 (color), 0.06 (B/W)	0.5 (color), 0.08 (B/W)	0.5 (color), 0.08 (B/W)	6 mm: 0.1 (color), 0.02 (B/W) 12 mm: 0.15 (color), 0.03 (B/W)
Video compression	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG
Max video resolution (pixels)	640 x 480	1280 x 800 (1 MP) ⁽²⁾	800 x 600	800 x 600	1280 x 800 (1 MP) ⁽²⁾	1280 x 800 (1 MP) ⁽²⁾	2048 x 1536 (3 MP)	2048 x 1536 (3 MP)	800 x 600
Frames per second (60/50 Hz)	30 (640x480)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (1280x800) 30 (HDTV 720p)	20 (2048x1536) 30 (HDTV 1080p) 30 (1600x1200)	20 (2048x1536) 30 (HDTV 1080p) 30 (1600x1200)	30/25 (800x600)
Audio support	Two-way, Built-in mic	Two-way, Built-in mic	Two-way, Built-in mic	Two-way	Two-way, Built-in mic	Two-way	Two-way, Built-in mic	Two-way	
Alarm in-/outputs	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	
Intelligent video	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC PoE IEEE 802.3af Class 2	DC PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 3	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 3	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2
Serial connectors									
Outdoor use				Outdoor ready		Outdoor ready		Outdoor ready	
Other	Tamper resistant ^(a) Vandal resistant ^(b) WDR, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™ (3:4 only)	Tamper resistant ^(a) Vandal resistant ^(b) WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Tamper resistant ^(a) , Vandal resistant ^(b) , WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Tamper resistant ^(a) , Vandal resistant ^(b) , WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Vandal resistant IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Tamper resistant ^(a) Vandal resistant ^(b) , WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽¹⁾ , ONVIF, Corridor Format™	Tamper resistant, WDR, digital PTZ, pixel counter, SD/SDHC card slot, Lightfinder technology, AVHS ⁽¹⁾ , ONVIF, Corridor Format™
Axis Part #	0290-001 ^(a) , 0292-001 ^(b)	0352-001 ^(a) , 0353-001 ^(b)	6mm: 0307-001 ^(a) , 0308-001 ^(b) 12mm: 0307-031 ^(a) , 0308-031 ^(b)	6mm: 0299-001 12mm: 0299-031	6mm: 0326-001 ^(a) , 0327-001 ^(b) 12mm: 0326-041 ^(a) , 0327-041 ^(b)	6mm: 0325-001 12mm: 0325-041	0369-001 ^(a) , 0370-001 ^(b)	0371-001	6mm: 0464-001 12mm: 0466-001
MSRP	\$599 ^(a) , \$639 ^(b)	\$699 ^(a) , \$739 ^(b)	6mm: \$799 ^(a) , \$839 ^(b) 12mm: \$799 ^(a) , \$839 ^(b)	6mm: \$999 12mm: \$999	6mm: \$899 ^(a) , \$939 ^(b) 12mm: \$899 ^(a) , \$939 ^(b)	6mm: \$1099 12mm: \$1099	\$959 ^(a) \$999 ^(b)	\$1159	6mm: \$599 12mm: \$599









Notations (a) and (b) refer to the corresponding product models for the column; (1) AVHS - AXIS Video Hosting System with One-Click Camera Connection; (2) 1440 x 900 (1.3 MP) scaled resolution available via VAPIX®

Axis fixed dome network cameras

Axis pan/tilt/zoom network cameras







Axis fixed dome network cameras					Axis pan/tilt/zoom network cameras			
	AXIS P3354	AXIS P3363-V ^(a) AXIS P3363-VE ^(b)	AXIS P3364-V ^(a) AXIS P3364-VE ^(b)	AXIS P3367-V ^(a) AXIS P3367-VE ^(b)	AXIS 212 PTZ ^(a) AXIS 212 PTZ-V ^(b)	AXIS M50 Series		AXIS 214 PTZ
								
Image sensor	Progressive scan RGB CMOS 1/3"	Progressive scan RGB CMOS 1/3"	Progressive scan RGB CMOS 1/3"	1/3.2" progressive scan CMOS	1/2" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" ExView HAD CCD
Lens	Varifocal, remote focus and zoom, IR corrected, P-Iris 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4	Varifocal, remote focus and zoom, IR corrected, P-Iris 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4	Varifocal, remote focus and zoom, IR corrected, P-Iris 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4	Varifocal, P-Iris, remote focus and zoom 3-9 mm/F1.2	2.7 mm/F1.8 fixed iris 3x instant zoom	3.6 mm/F1.8 3x digital zoom	3.6 mm/F1.8 3x digital zoom	4.1 - 73.8 mm/F1.3 auto iris and autofocus 18x optical zoom 12x digital zoom
Horizontal angle of view	6 mm: 105°-49° 12 mm: 82°-24°	6 mm: 105°-49° 12 mm: 82°-24°	6 mm: 105°-49° 12 mm: 82°-24°	84° - 30°	140° - 44°	45°	60°	48° - 2.7°
Day and night	Automatic	Automatic	Automatic	Automatic				Automatic
Min illumination/ light sensitivity (lux)	6 mm: 0.1 (color), 0.02 (B/W) 12 mm: 0.15 (color), 0.03 (B/W)	6 mm: 0.1 (color), 0.02 (B/W) 12 mm: 0.15 (color), 0.03 (B/W)	6 mm: 0.1 (color), 0.02 (B/W) 12 mm: 0.15 (color), 0.03 (B/W)	0.2 (color), 0.04 (B/W)	10 lux wide mode 20 lux tele mode	1.4 (color)	1.4 (color)	0.3 (color) 0.005 (B/W)
Video compression	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	1280x960 (approx. 1.3 MP) ⁽³⁾	800x600	1280x960 (approx. 1.3 MP) ⁽³⁾	2592x1944 (5 MP)	640x480	SVGA 800x600	HDTV 720p 1280x720	4CIF: 704x480 (60 Hz), 704x576 (50 Hz)
Frames per second (60/50 Hz)	30/25 (1280x960)	30/25 (800x600)	30/25 (1280x960)	12(2592x1944) 20 (2048x1536) 30 (HDTV 1080p) 30 (1600x1200)	30 (640x480) at max. zoom	30	30	30/25 (4CIF)
Pan/Tilt/Zoom					20 presets 140° pan 105° tilt Guard tour	25 presets ±180° pan 90° tilt	25 presets ±180° pan 90° tilt	20 presets 340° pan 120° tilt
Audio support		Two-way	Two-way	Two-way	Two-way, built-in mic	One-way, built-in mic	One-way, built-in mic	Two-way
Alarm in-/outputs		1/1	1/1	1/1	1/1			1/1
Intelligent video	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection	Motion detection, audio detection, AXIS Camera Application Platform	Motion detection, audio detection, AXIS Camera Application Platform	Motion detection Audio detection
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 3	PoE IEEE 802.3af Class 3	PoE IEEE 802.3af Class 3	DC PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 3	PoE IEEE 802.3af Class 3	DC
Serial connectors								
Outdoor use		Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)				Requires housing
Other	Tamper resistant, WDR, digital PTZ, pixel counter, SD/SDHC card slot, Lightfinder technology, AVHS ⁽²⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, SD/SDHC card slot, Lightfinder technology, AVHS ⁽²⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, SD/SDHC card slot, Lightfinder technology, AVHS ⁽²⁾ , ONVIF, Corridor Format™	Vandal resistant, IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, SD/SDHC card slot, AVHS ⁽²⁾ , ONVIF, Corridor Format™	Continuous motion 24/7, Vandal resistant ^(b) , ONVIF, AVHS ⁽²⁾	AVHS ⁽²⁾ , pixel counter, IP51 rating, MicroSDHC card slot, ONVIF	AVHS ⁽²⁾ , pixel counter, IP51 rating, MicroSDHC card slot, ONVIF	AVHS ⁽¹⁾
Axis Part #	6 mm: 0465-001 12 mm: 0467-001	6 mm: 0508-001 ^(a) , 0468-001 ^(b) 12 mm: 0470-001 ^(a) , 0483-001 ^(b)	6 mm: 0481-001 ^(a) , 0482-001 ^(b) 12 mm: 0471-001 ^(a) , 0484-001 ^(b)	0406-001 ^(a) 0407-001 ^(b)	0257-004 ^(a) 0280-004 ^(b)	0398-001	0399-001	0246-004
MSRP	6 mm: \$699 12 mm: \$699	6 mm: \$699 ^(a) , \$859 ^(b) 12 mm: \$699 ^(a) , \$859 ^(b)	6 mm: \$799 ^(a) , \$959 ^(b) 12 mm: \$799 ^(a) , \$959 ^(b)	\$1159 ^(a) \$1319 ^(b)	\$649 ^(a) , \$699 ^(b)	\$499	\$599	\$1299

Axis pan/tilt/zoom network cameras

	AXIS P55 Series					AXIS Q60 Series		
	AXIS P5512 ^(a) AXIS P5512-E ^(b)	AXIS P5522 ^(a) AXIS P5522-E ^(b)	AXIS P5532 ^(a) AXIS P5532-E ^(b)	AXIS P5534 ^(a) AXIS P5534-E ^(b)	AXIS P5544	AXIS Q6032 ^(a) AXIS Q6032-E ^(b)	AXIS Q6034 ^(a) AXIS Q6034-E ^(b)	AXIS Q6035 ^(a) AXIS Q6035-E ^(b)
								
Image sensor	1/4" CCD	1/4" ExViewHAD progressive scan CCD	1/4" ExViewHAD progressive scan CCD	1/3" progressive scan CCD	1/3" progressive scan CCD	1/4" ExView HAD progressive scan CCD	1/3" progressive scan CCD	1/2.8 progressive scan CMOS
Lens	3.8 – 46 mm/F1.6 autofocus 12x optical zoom 4x digital zoom	4.1 – 73.8 mm/F1.4 auto iris and autofocus 18x optical zoom 12x digital zoom	3.6 – 104.4 mm/F1.43 auto iris and autofocus 29x optical zoom 12x digital zoom	4.7 – 84.6 mm/F1.6 auto iris and autofocus 18x optical zoom 12x digital zoom	Zoom lens: 4.7 – 84.6 mm/F1.6 auto iris and autofocus 18x optical zoom, 12x digital zoom, Panopsis lens: 2.7 mm	3.4 – 119 mm/F1.4 auto iris and autofocus 35x optical zoom 12x digital zoom	4.7 – 84.6 mm/F1.6 auto iris and autofocus 18x optical zoom 12x digital zoom	4.7 – 94 mm/F1.6 auto iris and autofocus 20x optical zoom 12x digital zoom
Horizontal angle of view	51.6° – 4.4°	47.0° – 2.8°	53.1° – 2.0°	55.2° – 3.2°	Zoom lens: 55.2° – 3.2° Panopsis lens: 180°	55.8° – 1.7°	55.2° – 3.2°	54.1° – 2.9° in HDTV 1080p 37.6° – 2° in HDTV 720p
Day and night	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	1 (color) 0.3 (B/W)	0.5 (color) 0.01 (B/W)	0.5 (color) 0.01 (B/W)	0.74 (color) 0.04 (B/W)	0.74 (color) 0.04 (B/W)	0.5 (color) 0.008 (B/W)	0.74 (color) 0.04 (B/W)	0.8 (color) 0.04 (B/W)
Video compression	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG
Max video resolution (pixels)	4CIF: 704x480 (60 Hz) 704x576 (50 Hz)	D1: 720x480 (60 Hz) 720x576 (50 Hz)	D1: 720x480 (60 Hz), 720x576 (50 Hz)	HDTV 720p 1280 x 720	HDTV 720p 1280 x 720	752x480 (60 Hz) ^(a) 736x576 (50 Hz) ^(a) D1: 720x480 (60 Hz) ^(b) 720x576 (50 Hz) ^(b)	HDTV 720p 1280 x 720	HDTV 1080p 1920x1080
Frames per second (60/50 Hz)	30/25 (4CIF)	30/25 (D1)	30/25 (D1)	30/25 (HDTV 720p)	30/25 (HDTV 720p)	30/25 (Extended D1) ^(a) 30/25 (D1) ^(b)	30/25 (HDTV 720p)	H.264: 30/25 (HDTV 1080p) H.264: 60/50 (HDTV 720p)
Pan/Tilt/Zoom	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets, 360° endless pan 180° tilt ^(a) , 220° tilt ^(b) , Guard tour, Tour recording ^(a)	100 presets 360° endless pan 180° tilt ^(a) , 220° tilt ^(b) Guard tour	100 presets 360° endless pan 180° tilt ^(a) , 220° tilt ^(b) Guard tour, Tour recording
Audio support	Two-way ^(a)	Two-way ^(a)	Two-way ^{(1)(a)}	Two-way ^{(1)(a)}	Two-way ⁽¹⁾	Two-way ^{(1)(a)}	Two-way ^{(1)(a)}	Two-way ^{(1)(a)}
Alarm in-/outputs	4 configurable inputs/ outputs ^{(1)(a)}	4 configurable inputs/ outputs ^{(1)(a)}	4 configurable inputs/ outputs ^{(1)(a)}	4 configurable inputs/ outputs ^{(1)(a)}	4 configurable inputs/ outputs ⁽¹⁾	4 configurable inputs/outputs ^{(1)(a)}	4 configurable inputs/outputs ^{(1)(a)}	4 configurable inputs/outputs ^{(1)(a)}
Intelligent video	Motion detection Audio detection ^(a) Advanced Gatekeeper AXIS Camera Application Platform	Motion detection Audio detection ^(a) Advanced Gatekeeper AXIS Camera Application Platform	Motion detection Audio detection ^(a) Advanced Gatekeeper AXIS Camera Application Platform ^(b)	Motion detection Audio detection ^(a) Advanced Gatekeeper AXIS Camera Application Platform ^(b)	Motion detection Audio detection ⁽¹⁾ Advanced Gatekeeper AXIS Camera Application Platform ^(b)	Motion detection, Audio detection ^(a) Auto-tracking, Active Gatekeeper ^(a) AXIS Camera Application Platform	Motion detection, Audio detection ^(a) Advanced Gatekeeper ^(a) , Auto-tracking ^(b) Active Gatekeeper ^(b) AXIS Camera Application Platform ^(b)	Motion detection, Audio detection ^(a) Auto-tracking, Active Gatekeeper AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	AC/DC ^{(1)(a)} PoE IEEE 802.3af Class 3	AC/DC ^{(1)(a)} PoE+ IEEE 802.3at (Midspan supplied)	AC/DC ^{(1)(a)} PoE+ IEEE 802.3at (Midspan supplied)	AC/DC ^{(1)(a)} PoE+ IEEE 802.3at (Midspan supplied)	AC/DC ⁽¹⁾ PoE+ IEEE 802.3at (Midspan supplied)	AC/DC ^{(1)(a)} PoE+ IEEE 802.3at (Midspan supplied) ^(a) High PoE (Midspan supplied) ^(b)	AC/DC ^{(1)(a)} PoE+ IEEE 802.3at ^(a) , High PoE ^(b) , (Midspan supplied)	AC/DC ^{(1)(a)} PoE+ IEEE 802.3at ^(a) , High PoE ^(b) , (Midspan supplied)
Outdoor use	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)
Other	Pixel counter, SD/SDHC slot, IP51 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , AVHS ⁽²⁾ , ONVIF	Pixel counter, SD/SDHC slot, IP51 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , WDR, AVHS ⁽²⁾ , ONVIF	Pixel counter, SD/SDHC slot, IP51 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , image stabilizer, WDR, AVHS ⁽²⁾ , ONVIF ^(b)	Pixel counter, SD/SDHC slot, IP51 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , WDR, AVHS ⁽²⁾ , ONVIF ^(b)	360° panoramic view, pixel counter, SD/SDHC slot, IP52 rating, WDR, AVHS ⁽²⁾ , ONVIF	Continuous motion 24/7, pixel counter, SD/SDHC slot, IP52 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , image stabilizer, WDR, AVHS ⁽²⁾ , Arctic Temperature Control ^(b)	Continuous motion 24/7, pixel counter, SD/SDHC slot, IP52 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , WDR, AVHS ⁽²⁾ , ONVIF, Arctic Temperature Control ^(b)	Continuous motion 24/7, pixel counter, SD/SDHC slot, IP52 rating ^(a) , IP66 and NEMA 4X ratings ^(b) , WDR, AVHS ⁽²⁾ , ONVIF, Arctic Temperature Control ^(b)
Axis Part #	0409-001 ^(a) , 0411-001 ^(b)	0420-004 ^(a) , 0422-004 ^(b)	0310-004 ^(a) , 0312-004 ^(b)	0314-004 ^(a) , 0316-004 ^(b)	0443-004	0357-004 ^(a) , 0318-004 ^(b)	0363-004 ^(a) , 0362-004 ^(b)	0444-004 ^(a) , 0445-004 ^(b)
MSRP	\$1099 ^(a) , \$1499 ^(b)	\$1499 ^(a) , \$1899 ^(b)	\$1999 ^(a) , \$2399 ^(b)	\$2499 ^(a) , \$2899 ^(b)	\$2999	\$2599 ^(a) , \$3199 ^(b)	\$2999 ^(a) , \$3599 ^(b)	\$3399 ^(a) , \$3999 ^(b)

Notations (a) and (b) refer to the corresponding product models for the column; (1) With multi-connector cable - sold separately; (2) AVHS - AXIS Video Hosting System with One-Click Camera Connection




Axis thermal network cameras






AXIS Q19 Series						
	 AXIS Q1910	 AXIS Q1910-E	 AXIS Q1921	 AXIS Q1921-E	 AXIS Q1922	 AXIS Q1922-E
Image sensor	Uncooled Micro bolometer	Uncooled Micro bolometer	Uncooled Micro bolometer	Uncooled Micro bolometer	Uncooled Micro bolometer	Uncooled Micro bolometer
Lens	13 mm/F1.25	13 mm/F1.25	10 mm/F1.2 19 mm/F1.0	10 mm/F1.2 19 mm/F1.0 35 mm/F1.2 60 mm/F1.2	10 mm/F1.2 19 mm/F1.0	10 mm/F1.2 19 mm/F1.0 35 mm/F1.2 60 mm/F1.2
Horizontal angle of view	17°	17°	10 mm: 55° 19 mm: 29°	10 mm: 55° 19 mm: 29° 35 mm: 15° 60 mm: 9°	10 mm: 55° 19 mm: 29°	10 mm: 57° 19 mm: 32° 35 mm: 18° 60 mm: 10°
Detection range (m/yd.)	200/220 ^(a) 550/600 ^(b)	200/220 ^(a) 550/600 ^(b)	10 mm: 200/220 ^(a) 460/515 ^(b) 19 mm: 380/415 ^(a) 870/950 ^(b)	10 mm: 200/220 ^(a) 460/515 ^(b) 19 mm: 380/415 ^(a) 870/950 ^(b) 35 mm: 700/765 ^(a) 1610/1760 ^(b) 60 mm: 1200/1312 ^(a) 2760/3020 ^(b)	10 mm: 200/220 ^(a) 460/515 ^(b) 19 mm: 380/415 ^(a) 870/950 ^(b)	10 mm: 320/350 ^(a) 990/1083 ^(b) 19 mm: 580/634 ^(a) 1800/1969 ^(b) 35 mm: 1050/1148 ^(a) 3200/3500 ^(b) 60 mm: 1800/1970 ^(a) 5500/6015 ^(b)
Sensitivity	NetD < 100 mK	NetD < 100 mK	NetD < 100 mK	NetD < 100 mK	NetD < 100 mK	NetD < 100 mK
Video compression	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	160 x 128	160 x 128	384 x 288	384 x 288	640 x 480	640 x 480
Frames per second	8.3	8.3	8.3/30 ⁽¹⁾	8.3/30 ⁽¹⁾	8.3/30 ⁽¹⁾	8.3/30 ⁽¹⁾
Audio support	Two-way Built-in mic	Two-way	Two-way Built-in mic	Two-way	Two-way Built-in mic	Two-way
Alarm in-/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs
Intelligent video	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3
Serial connectors	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485
Outdoor use	Requires housing designed for thermal cameras	Outdoor ready	Requires housing designed for thermal cameras	Outdoor ready	Requires housing designed for thermal cameras	Outdoor ready
Other	Palette setting, SD/SDHC card slot, ONVIF, AVHS ⁽²⁾	IP66 rating, palette setting, SD/SDHC card slot, ONVIF, AVHS ⁽²⁾	Palette setting, SD/SDHC card slot, ONVIF, AVHS ⁽²⁾	IP66 rating, palette setting, SD/SDHC card slot, ONVIF, AVHS ⁽²⁾	Palette setting, SD/SDHC card slot, ONVIF, AVHS ⁽²⁾	IP66 rating, palette setting, SD/SDHC card slot, ONVIF, AVHS ⁽²⁾
Axis Part #	0334-001	0335-001	10mm: 0388-001 19mm: 0384-001	10mm: 0389-001 19mm: 0385-001 35mm: 0390-001 60mm: 0391-001	10mm: 0506-001 19mm: 0502-001	10mm: 0507-001 19mm: 0503-001 35mm: 0477-007 60mm: 0478-001
MSRP	\$2999	\$3499	10mm: \$3999 19mm: \$3999	10mm: \$4499 35mm: \$5399 19mm: \$4499 60mm: \$7599	10mm: \$8499 19mm: \$8499	10mm: \$8999 35mm: \$9899 19mm: \$8999 60mm: \$12099

Notifications (a) and (b) refer to detection range measured for (a) humans 1.8 m x 0.5 m and (b) Vehicles 2.3 x 2.3 m;

(1) 30 fps available for EU001 compliant countries such as U.S. and Canada; (2) AVHS - AXIS Video Hosting System with One-Click Camera Connection

Accessories

Illuminators		
		
White light and infrared illuminators for indoor/outdoor surveillance in low light or complete darkness. FixedDome IR-LEDs for outdoor versions of AXIS P33 Series.		
AXIS T90A01 850nm 50 Deg PoE	5013-011	\$449
AXIS T90A11 850nm 50 Deg	5013-111	\$449
AXIS T90A16 W-LED 50 Deg	5013-161	\$449
AXIS T90A20 850nm 120-180 Deg	5013-201	\$499
AXIS T90A21 850nm 50-100 Deg	5013-211	\$499
AXIS T90A26W-LED-100 Deg	5013-261	\$599
AXIS T90A32 850nm 30-60 Deg	5013-321	\$1199
AXIS T90A33 850nm 10-20 Deg	5013-331	\$1199
AXIS T90A37 W-LED 30-60 Deg	5013-371	\$1199
AXIS T90A40 850nm 120-180 Deg	5013-401	\$1699
AXIS T90A42 850nm 30-60 Deg	5013-421	\$1699
AXIS T90C10 Fixed Dome IR-LED	5024-101	\$349
AXIS T90C20 Fixed Dome IR-LED	5024-201	\$349
Power over Ethernet Midspans and Splitters		
		
Axis Power over Ethernet (PoE) and High PoE midspans and splitters offer an easy, cost-effective solution for powering network video products without the need for power outlets and electrical cabling.		
Power over Ethernet Midspans		
1-port	0226-004	\$69
High PoE 1-port (30 W)	5014-204	\$89
High PoE 1-port (60 W)	5700-401	\$149
8-port	5012-004	\$599
16-port	5012-014	\$799
Power over Ethernet Active Splitters		
High PoE 12V	5014-501	\$89
High POE 24V	5014-511	\$89
5V	5008-001	\$59
Pan-Tilt Motor		
		
YP3040 Pan-Tilt Motor can be used with AXIS Q1755, AXIS Q1910/-E and AXIS Q1921 cameras to enable basic pan and tilt capability. The motor can be mounted on walls, both indoors and outdoors.		
	5502-461	\$499

AXIS T8310 Video Surveillance Control Board	
	
AXIS T8310 Control Board is a modular system comprising of AXIS T8311 Joystick, which gives accurate control of PTZ functions of network cameras; AXIS T8312 Keypad, used for navigating between workspaces, cameras, views and PTZ presets; AXIS T8313 Jog Dial, used for navigating through recorded video. Each unit can be purchased and used separately or together.	
	5020-001 \$1149
AXIS P7701 Video Decoder	
	
AXIS P7701 Video Decoder provides a simple monitoring solution by enabling analog or digital monitors to connect to and display live video from Axis network cameras and video encoders.	
	0319-004 \$499
AXIS P8221 Network I/O Audio Module	
	
AXIS P8221 provides eight I/O ports and audio capabilities to a network video surveillance system that either does not have such support or requires additional support.	
	0321-004 \$349
AXIS T8414 Installation Display	
	
AXIS T8414 is a battery-powered handheld device that greatly simplifies image setting adjustments, PTZ control, video clip recordings and playback of clips previously downloaded or recorded with AXIS T8414. Snapshots and video clips can be saved to internal memory, or to a connected MicroSD or USB device.	
	5900-144 \$649
AXIS Q8108-R Network Video Recorder	
	
AXIS Q8108-E is an 8-channel network video recorder (NVR) specially designed for public and commercial transportation applications. It provides uninterrupted in-vehicle recording in full frame rate HDTV resolution for up to 8 connected cameras.	
	0332-031 \$3799

Axis network camera housings











Part #	Product	Compatible with:	MSRP
5015-101 ^(a) 5015-204 ^(b)	AXIS T92A10^(a) / T92A20^(b) Housing Aluminum construction - Indoor/outdoor	AXIS 211W, AXIS 221, AXIS P1343, AXIS P1344, AXIS P1346, AXIS P1347, AXIS Q16 Series, AXIS Q1755	\$299 ^(a) \$449 ^(b)
0217-031	VT Wall bracket Internal Cable WBOVA1		\$36
0217-101	VT Corner Mount WCWA	AXIS T92A10/T92A20	\$59
0217-081	VT Pole Mount Adapter WSFPA		\$68
0217-051	VT Ceiling Bracket Internal Cable WCM4A		\$109
5010-001 ^(a) 5010-101 ^(b)	Dome Housing AXIS T95A00 110/240V AC^{(a)(1)} / T95A10 24V AC^{(b)(2)} Aluminum construction - Indoor/outdoor	AXIS 214 PTZ, AXIS 233D	\$649 ^(a) \$599 ^(b)
5010-611	AXIS T95A61 Wall Bracket	Wall Bracket for AXIS T95A00 and T95A10 Dome Housing.	\$99
5010-641	AXIS T95A64 Corner Bracket	Requires AXIS T95A61 Wall Bracket.	\$89
5010-671	AXIS T95A67 Pole Bracket	Requires AXIS T95A61 Wall Bracket.	\$129
24886	AXIS Indoor Fixed Wall Housing	AXIS M1103, AXIS M1104, AXIS M1113, AXIS M1114, AXIS 221, AXIS P1343, AXIS P1344, AXIS P1346, AXIS P1347, AXIS Q1755	\$299
24887	AXIS Indoor Fixed Corner Housing		\$299
24888	AXIS Indoor Fixed Ceiling Housing		\$199
21899 ^(a) 24889 ^(b)	AXIS Fixed Housing - Indoor^(a) / Outdoor^(b) Aluminum construction - Indoor/outdoor	AXIS M1103 ^(a) , AXIS M1104 ^(a) , AXIS M111 ^(a) , AXIS M1113, AXIS M1114 ^(a) , AXIS 211W, AXIS 221, AXIS P1343, AXIS P1344, AXIS P1346, AXIS P1347, AXIS Q1755	\$149 ^(a) \$299 ^(b)
22870	AXIS Indoor Fixed Camera Dome	AXIS 211W, AXIS 221, AXIS P1343, AXIS P1346, AXIS P1347, AXIS Q1755	\$199
29892	AXIS Fixed Wireless Housing Aluminum construction - Outdoor	AXIS 211W	\$499
25735 ^(a) 35540 ^(b)	AXIS Pendant Dome Indoor - Clear^(a) / Smoked^(b)	AXIS 214 PTZ, AXIS 233D	\$299 ^(a) \$299 ^(b)
25733 ^(a) 35541 ^(b)	AXIS Pendant Dome Outdoor - Clear^(a) / Smoked^(b)	AXIS 214 PTZ, AXIS 233D	\$599 ^(a) \$599 ^(b)
25734 ^(a) 35542 ^(b)	AXIS Pendant Vandal Dome - Clear^(a) / Smoked^(b) Aluminum construction - Indoor/outdoor	AXIS 214 PTZ, AXIS 233D	\$849 ^(a) \$849 ^(b)

(1) 110 VAC input power; (2) Requires AXIS PS-24 power supply (5000-001);
 (3) AXIS Q6032-E Pendant Kit included; (4) Requires mounting tool (21776);
 (5) Requires 1.5" NPT threaded brackets; (6) Requires separate PoE power source




For more information, visit www.axis.com/products/video/accessories

Part #	Product	Compatible with:	MSRP
25736	Gooseneck Wall Mount	Gooseneck wall mount for the AXIS Pendant Dome	\$99
25738	Parapet Mount	Parapet mount for the AXIS Pendant Dome	\$399
22059	Corner Mount Adapter	Corner mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings	\$89
21896	Pole Mount Adapter	Pole mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings.	\$59
26349 ^(a) 26350 ^(b)	Ceiling Mount Extension 12"^(a)/24"^(b)	Secures AXIS Pendant Dome housings to hard ceilings	\$149 ^(a) \$169 ^(b)
5017-611	AXIS T91A61 Wall Bracket⁽³⁾ Includes mounting plate - White	AXIS 216FD Pendant Kit, AXIS P33 Series Pendant Kit, AXIS P33-VE Series Pendant Kit, AXIS P5532, AXIS 5532-E, AXIS P5534, AXIS P5534-E, AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E	\$99
5017-621	AXIS T91A62 Parapet Mount⁽⁵⁾		\$189
5017-631	AXIS T91A63 Ceiling Bracket⁽⁵⁾		\$119
5017-671	AXIS T91A67 Pole Bracket⁽⁵⁻⁴⁾		\$99
5017-641	AXIS T91A64 Corner Bracket	Requires AXIS T91A61 Wall Bracket.	\$79
5502-431	AXIS Q6032-E Pendant Kit	AXIS P5532, AXIS P5532-E, AXIS P5534, AXIS P5534-E, AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E	\$49
5502-351	AXIS P33 Series Pendant Kit	AXIS P3343, AXIS P3344, AXIS P3343-V, AXIS P3344-V, AXIS P3346, AXIS P3346-V, AXIS P3367-V	\$39
5502-321	AXIS P33-VE Series Pendant Kit	AXIS P3343-VE, AXIS P3344-VE, AXIS P3346-VE, AXIS P3367-VE	\$49
5502-021 ^(a) 5502-011 ^(b)	AXIS 216FD Pendant Kit⁽⁵⁾ - White^(a) / Black^(b)	AXIS M3203, AXIS M3203-V, AXIS M3204, AXIS M3204-V, AXIS P3301, AXIS P3301-V, AXIS P3304, AXIS P3304-V	\$39 ^(a) \$39 ^(b)
0344-001	AXIS T92E05 Protective Housing	AXIS M11 Series, AXIS P13 Series, AXIS Q1755	\$199
0433-001	AXIS T92E20 Outdoor Housing	AXIS M1113, AXIS M1114, AXIS P1344, AXIS P1346, AXIS P1347, AXIS Q1755	\$329
5502-871	AXIS T93E05 Protective Housing	AXIS M11 Series	\$120
0386-001	AXIS T92E23 Thermal Camera Housing	AXIS Q1910 and AXIS Q1921 with 10mm, 19mm or 35mm lens	\$899
0387-001	AXIS T92E24 Thermal Camera Housing	AXIS Q1921 with 60mm lens	\$1599
5021-101	AXIS T97A10 Enclosure	AXIS Q7401, AXIS P8221, AXIS P7701	\$84

Axis video encoders

	4-channel video encoders									
	AXIS 243SA ^(5,6)	AXIS M7001 ^(2,4,5,6)	AXIS Q7401 ^(3,4,5,6)	AXIS 243Q	AXIS M7014 ^(3,4,5,7)	AXIS P7214 ^(4,5,7)	AXIS P7224 ^(3,4,5,7)	AXIS Q7404 ^(4,5)	AXIS Q7414 ^(4,5)	AXIS Q7424-R
										
Video compression	MPEG-4 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	4CIF: 704x480 (NTSC) 704x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	4CIF: 704x480 (NTSC) 704x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)
Frames per second H.264 (NTSC/PAL) in maximum resolution		30/25 (D1)	30/25 (D1)		15 (D1) per channel	30/25 (D1) per channel	30/25 (D1) per channel	30/25 (D1)	30/25 (D1) per channel	30/25 (D1) per channel
Frames per second Motion JPEG (NTSC/PAL) in maximum resolution	30/25 (4CIF)	30/25 (D1)	30/25 (D1)	30/25 (4CIF) per channel	15 (D1) per channel	30/25 (D1) per channel	30/25 (D1) per channel	30/25 (D1)	30/25 (D1) per channel	30/25 (D1) per channel
Frames per second MPEG-4 (NTSC/PAL) in maximum resolution	30/25 (4CIF)			30/25 (4CIF) per channel						
Video source	1 BNC composite or Y/C video input ⁽¹⁾	1 BNC composite input	1 BNC composite input	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs
Audio support	Two-way		Two-way			Two-way	Two-way	Two-way on one channel	Two-way	Two-way
Alarm in-/outputs	4/4		4 configurable inputs/outputs	4/4		4 configurable inputs/outputs	4 configurable inputs/outputs	2 configurable inputs/outputs per channel	2 configurable inputs/outputs per channel	4 configurable inputs/outputs
Intelligent video	Motion detection Audio detection Tampering alarm	Motion detection	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform
Pan/tilt/zoom support	●	●	●	●	●	●	●	●	●	●
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption, IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC	PoE IEEE 802.3af Class 2, supports power output for small covert camera	DC PoE IEEE 802.3af Class 2/3, supports power output for analog camera		DC PoE IEEE 802.3af Class 3	DC PoE IEEE 802.3af Class 3		DC		DC PoE IEEE 802.3af Class 3
Serial connectors	RS-232, RS-485	RS-422/RS-485	RS-422/RS-485	RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485
Standalone version	0256-004	0298-001	0288-004		0415-004	0417-004		0291-004		0487-001
Blade version				0261-001			0418-001		0354-001	
MSRP	\$699	\$299	\$399	\$999	\$499	\$699	\$699	\$1099	\$1199	\$1199

Axis video encoders

	AXIS M7010 ^(1,2,3,4)	AXIS P7210 ^(1,2,3,4)	AXIS Q7406 ^(2,3)
			
Video compression	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)	D1: 720x480 (NTSC) 720x576 (PAL)
Frames per second H.264 (NTSC/PAL) in maximum resolution	15 (D1) per channel	30/25 (D1) per channel	30/25 (D1) per channel
Frames per second Motion JPEG (NTSC/PAL) in maximum resolution	15 (D1) per channel	30/25 (D1) per channel	30/25 (D1) per channel
Frames per second MPEG-4 (NTSC/PAL) in maximum resolution			
Video source	16 BNC composite inputs	16 BNC composite inputs	6 BNC composite inputs
Audio support		Two-way	
Alarm in-/outputs		4 configurable inputs/outputs	2 configurable inputs/outputs
Intelligent video	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Tampering alarm AXIS Camera Application Platform
Pan/tilt/zoom support	●	●	●
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC, PoE IEEE 802.3af Class 3	DC, PoE IEEE 802.3af Class 3	
Serial connectors	RS-422/RS-485	RS-422/RS-485	RS-485
Standalone version	0414-004	0416-004	
Blade version			0289-001
MSRP	\$1999	\$2499	\$1499

Notations (a) and (b) refer to the corresponding product models for the column; (1) Supports local storage with SD/SDHC card; (2) ONVIF Compliant; (3) AVHS-AXIS Video Hosting System with One-Click Connection; (4) Quad-view.

Technical Services



Axis stays with you all the way.

At Axis, we help our partners and end customers find solutions. Start with our support web at www.axis.com/support for your product questions. With more than 400 FAQs in our extensive database, you are sure to find the product details you need. You can also submit advanced queries related to your Axis solution using the Online Helpdesk.



Rack Solutions

Designed for high-density installations, Axis video encoder rack solutions accommodate multiple video encoder blades in the same rack.

	AXIS 291 1U Video Server Rack	AXIS Q7900 Rack
		
Number of slots	3	14
Blades supported	AXIS 241Q, AXIS 241S, AXIS 243Q, AXIS Q7406, AXIS Q7414, AXIS P7224	AXIS 241Q, AXIS 241S, AXIS 243Q, AXIS Q7406, AXIS Q7414, AXIS P7224
Maximum number of channels	18	84
Rack size	1U	4U
Rack width	19"	19"
Built-in power supply	Power supply	Two redundant power supplies
Network	One Ethernet 10BASE-T/ 100BASE-TX/1000BASE-T (Gigabit Ethernet) port	Four Ethernet 10BASE-T/ 100BASE-TX/1000BASE-T (Gigabit Ethernet) ports
Axis Part #	0267-004	0287-004
MSRP	\$399	\$2999

For more information, visit www.axis.com/products/video/video_server/

Video management software

AXIS Camera Station		
AXIS Camera Station is a complete monitoring and recording system that is perfect for small- to mid-sized installations. It offers easy installation and setup with automatic camera discovery, a powerful Configuration Wizard and efficient management of the Axis network video products in the system.		
10-camera base license	0202-004	\$999
4-camera base license	0202-054	\$649
20-camera add on license	0202-264	\$1979
5-camera add on license	0202-014	\$499
1-camera add on license	0202-034	\$99
1-year software upgrade	0202-024	\$149
AXIS Camera Management		
Powerful and efficient installation and management tool for Axis network video products. Available for free download.		
Axis' Application Development Partners		
A wide variety of software solutions for video surveillance, remote monitoring or broadcasting are available from more than 800 Axis Application Development Partners.		

Axis Certification Program



Take the challenge! Showcase your expertise in network video with the global standard for individual certification from Axis. Register for the Axis Certification Program - then pass our advanced-level test to become an Axis Certified Professional.

Axis offers both online and classroom-based training to help you acquire the knowledge needed to pass the exam. Go to www.axis.com/ certification to find our online learning center and for more information on how to register.

AXIS Video Hosting System

AXIS Video Hosting System (AVHS) enables a hosted monitoring and recording service to be managed and distributed to you by a service provider. With an Internet connection and an Axis camera as the only requirements, you can enjoy a trouble-free monitoring solution over the Internet.

For more information visit www.axis.com/hosting/

AXIS Camera Station One

Software solution for viewing and recording live video from a single Axis network camera. Available for free download.

For more information, visit www.axis.com/products/video/software/

AXIS Mobile Monitor

AXIS Mobile Monitor software enables smartphones or Pocket PCs to quickly and easily access live video from Axis network video products. Available for free download.

AXIS Camera Application Platform

AXIS Camera Application Platform enables compatible applications, typically intelligent video applications, to be downloaded to Axis network video products.

AXIS Camera Companion

AXIS Camera Companion is the market's easiest video surveillance solution. Perfect for small systems, it offers future-proof IP advantages such as HDTV image quality. With AXIS Camera Companion, all video is recorded on SD cards in the cameras, and no DVR or server is necessary

For more information, visit www.axis.com/products/cam_companion_software/

About Axis Communications

As the market leader in network video, Axis is leading the way to a smarter, safer, more secure world — driving the shift from analog to digital video surveillance. Offering network video solutions for professional installations, Axis' products and solutions are based on an innovative, open technology platform.

Axis has more than 1,000 dedicated employees in 40 locations around the world and cooperates with partners covering 179 countries. Founded in 1984, Axis is a Sweden-based IT company listed on NASDAQ OMX Stockholm under the ticker AXIS. For more information about Axis, please visit our website www.axis.com.

Distributed by: